



ROBOTIC TOW TRACTOR



**STRONG PARTNERS.
TOUGH TRUCKS.™**

Are you experiencing high operator turnover? Retain talent by automating mundane, repetitive tasks – focusing skilled operators on more engaging activities.

- Standard trailer handling configurations
- Sequencing in assembly operations
- Kitting separate items to be supplied as one unit
- Stock replenishment and hauling
- Reduce repeated operator training/onboarding costs
- Dual mode capabilities

GENERAL SPECIFICATIONS

| | | | |
|-------------|-------------------------------------|---------------|---|
| GENERAL | Model | | L07.0 |
| | Rated capacity | lb | 15,000 |
| | Operation Type | | Stand (manual) |
| | Power type | | Electric 24 volt |
| DIMENSIONS | Outside turning radius | in. | 11'6" |
| | Vertical clearance | ft./in. | 8'3" |
| | Travel path width (one-way traffic) | ft./in. | 6'5" (minimum) |
| | Travel path width (two-way traffic) | ft./in. | 11'2" (minimum) |
| PERFORMANCE | Travel speed (manual) | mph | 8.1 |
| | Travel speed (robotic) | mph | 4.5 |
| | Travel direction (manual) | | Forward and reverse |
| | Travel direction (robotic) | | Forward only |
| | Ramp elevation | | Inclines/Declines < 3% |
| POWER | Hitching to cart | | Auto-hitching and auto-unhitching |
| | Power source | | Lead-acid, lithium-ion, or hydrogen fuel cells |
| | Battery charging method | | Auto Charge available for certain power sources |
| | Battery compartment | L x W x H in. | 31.2" x 14.1" x 32" |

*Please refer to the L07.0 (base truck) specifications sheet for additional details

KEY ADVANTAGES OF THE HYSTER® ROBOTIC TOW TRACTOR



Cobotics: Allows people to focus on value added tasks, and robotic lift trucks on repetitive, low value added tasks.



Rapid Deployment: Runs with zero, partial or full integration with facility warehouse management systems (WMS).



Infrastructure Free Navigation: Integrates into existing operations by mapping structural features to self-locate and navigate; does not require laser reflectors, guide wire or magnets.



Flexible: Can switch to manual mode with the touch of a button, helping accommodate changing operational needs.




Scalable: Has the ability to take on small tasks and expand as operational requirements grow.

For questions about Hyster Robotics contact roboticssupport@hyster.com or call **844-337-1644**.



Visit us online at www.hyster.com or call us at **1-800-HYSTER-1**.

Hyster,  and STRONG PARTNERS. TOUGH TRUCKS. are registered trademarks in the United States and certain other jurisdictions. Hyster products are subject to change without notice. Trucks may be shown with optional equipment.
© 2020 Hyster Company. All rights reserved.